

Drying cabinet TS 4/TS 4 Basket



Drying cabinet TS 4

TS 4 is an excellent drying cabinet for smaller spaces such as day-care centers. The cabinet is only 60 cm (23,4 inch) wide and has big capacity. You can dry up to 4 kg (8,8 lbs) laundry. The TS 4 is equipped with pull-out hanging system. Flexible construction allows hanging bars to slide forward for easy access to garments or down for more space. The TS 4 Basket is equipped with 4 baskets, perfect for drying smaller items.

Easy to install; the evacuating channel is connected to the ventilation system and the humid air is transported out of the room. All electrical components are placed on the top which makes it easy to maintain. Simple manual control panel.



Standard equipment

- Capacity, up to 4 kg (8,8 lbs)
- Pull-out hanging system
- 3 temperatures; high, normal, low
- Energy efficient
- Easy control panel
- Timer adjustable up to 4 hours
- Overheat protection
- IP 24 classification. CE-approved
- The door can be ordered right or left handed

Optional extras

- Can be ordered with left-hand hanging frame
- Can be ordered with single rack bar
- Hook rack, set of three



Perfect for smaller places such as day-care centers



Ideal for delicate garments that are not suitable for tumble dryers.

Main specifications

	TS 4	TS 4 Basket
Loading capacity, kg/lbs	4/8,8	4/8,8
Drying capacity, g/min*	17	17
Hanging length, m/feet	16/52,5	-
Baskets	-	4
Drying time, economy 30° C, min*	180	180
Drying time, express 45° C, min*	120	120
Heating effect, kW	1,5	1,5
Total effect, kW	1,535	1,535
Energy consumption economy /kg, kWh	0,5	0,5
Energy consumption express /kg, kWh	0,6	0,6
Part No	131001	131007

*Valid for high-spinned textiles.

certway

PODAB uses Certways templates and guidelines for environmental and quality management in accordance with ISO 14001:2004 and ISO 9001:2008.



	TS 4	TS 4 Basket
Electrical connections		
Electrical connection*	1N, 230 V, 50 Hz	1N, 230 V, 50 Hz
Fuse, A	10	10
Total effect, kW	1,535	1,535
Heating elements, kW	1,5	1,5
Air connections		
Outlet exhaust, \varnothing mm/inch	100/3,94	100/3,94
Outlet air flow, m ³ /h	50	50
Pressure drop, max Pa**	60	60
Dewatering capacity, g/min	17	17
Sound level		
Airborne sound level, dB(A)	60	60
Shipping data		
Net, kg/lbs	61/134,5	61/134,5
Crated, kg/lbs	4/8,8	4/8,8
Shipping data net, kg/lbs	65/143	65/143
Shipping volume, m ³	0,2	0,2
Optional extras		
Air exchanger 1 vent., 125 mm/4,9 inch	141009	141009
Air exchanger 2 vent., 160 mm/6,3 inch	141018	141018
Dimensions		
Width, mm/inch	595/23,4	595/23,4
Depth, mm/inch	615/24,2	615/24,2
Height, mm/inch	1915/75,4	1915/75,4